



MS 6620-11-K-Z

- Thermoplastic enclosure
- without mounting flange

Data

Ordering data

Product type description	MS 6620-11-K-Z
Article number (order number)	101055458
EAN (European Article Number)	4030661006246
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

General data

Standards	EN IEC 60947-5-1
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	52 g

General data - Features

Number of normally closed (NC)	1
Number of normally open (NO)	1

Mechanical data

Mechanical life, minimum	3,000,000 Operations
Actuating speed, minimum	10 mm/min
Repeat accuracy of switching points	0.05

Mechanical data - Connection technique

Terminal designations	H05VV-F 3 x 0,75 mm ²
Wire cross-section	0.75 mm ²

Ambient conditions

Degree of protection	IP67
Ambient temperature	-30_+80

Ambient conditions - Insulation values

Rated insulation voltage U_i	250 VAC
Rated impulse withstand voltage U_{imp}	4 kV

Electrical data

Thermal test current	4 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	1 A
Switching principle	Snap action with self-cleaning contact
Switching frequency	30,000 /h
Material of the contacts, electrical	Gold-plated silver (AgNi 15 + Au 0,3µm)

Pictures

Product picture (catalogue individual photo)



ID: km661f01

| 172.9 kB | .jpg | 82.197 x 293.158 mm - 233 x 831 px - 72 dpi

| 197.5 kB | .png | 74.083 x 263.878 mm - 210 x 748 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 10/04/2023, 09:50