

\*\*\* spare part \*\*\* connection box DP plus for Mobile Panels (MPI/PROFIBUS)



General information	
Product function	
• Location identifier	Yes
FH technology	
Safety evaluation through direct wiring	
• Reconnection without emergency stop circuit interruption	Yes
• Monitoring the STOP button	Yes
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.5 A
Power	
Active power input, typ.	12 W
Interfaces	
Interfaces/bus type	1x RS 232, 1x RS 422, 1x RS 485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of RS 232 interfaces	1
Number of 20 mA interfaces (TTY)	0
Connection point identification	Yes
Degree and class of protection	
IP degree of protection	IP65
Standards, approvals, certificates	
CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No
Use in hazardous areas	
• ATEX Zone 2	No
• ATEX Zone 22	No
• FM Class I Division 2	No
Ambient conditions	
Ambient temperature during operation	
Operation (vertical installation)	

— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	70 °C
<b>Relative humidity</b>	
• Operation, max.	85 %
<b>Dimensions</b>	
Width	160 mm
Height	120 mm
Depth	70 mm
<b>Weights</b>	
Weight (without packaging)	0.4 kg
<b>Other</b>	
free hotline	Yes
<b>Usable in the following products</b>	
• Product 1	6AV6645-0A*
• Product 2	6AV6645-0C*
• Product 3	<a href="#">6AV6645-0BE02-0AX0</a>

**last modified:** 11/3/2021 